

ABSTRACT

A syringe (1) is moved bodily forward by a plunger (7) (after release of a spring 8) by acting through an O-ring pressing onto an enlarged head (16) of a syringe container (3), in order to expose the needle (5) of the syringe before the plunger acts on a plug (4) within the syringe to cause the liquid to be ejected through the needle. There is, therefore, a two-step movement of the plunger, firstly together with the syringe through the medium of the O-ring, and secondly within the syringe container to force the plug forward, when a ledge (12) on the syringe container (3) is arrested by a stop (14), whereupon the frictional force between the plunger and the O-ring is relieved so that the plunger slides forward through the O-ring.

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/002653 A1

(51) International Patent Classification⁷: A61M 5/32, 5/20

(21) International Application Number:
PCT/GB2004/002903

(22) International Filing Date: 5 July 2004 (05.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0315600.7 4 July 2003 (04.07.2003) GB

(71) Applicant (for all designated States except US): OWEN MUMFORD LIMITED [GB/GB]; Brook Hill, Woodstock, Oxfordshire OX20 1TU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ROLFE, Steven, Mark, Guy [GB/GB]; 18 Crosslands, Fringford, Bicester, Oxon OX27 8DF (GB). MARSHALL, Jeremy [GB/GB]; 16 Cranham Street, Jericho, Oxford OX2 6DD (GB).

(74) Agents: WYNNE-JONES, LAINE & JAMES et al.; Essex Place, 22 Rodney Road, Cheltenham GL50 1JJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: AUTOMATIC PEN-TYPE INJECTOR



(57) Abstract: A syringe (1) is moved bodily forward by a plunger (7) (after release of a spring 8) by acting through an O-ring pressing onto an enlarged head (16) of a syringe container (3), in order to expose the needle (5) of the syringe before the plunger acts on a plug (4) within the syringe to cause the liquid to be ejected through the needle. There is, therefore, a two-step movement of the plunger, firstly together with the syringe through the medium of the O-ring, and secondly within the syringe container to force the plug forward, when a ledge (12) on the syringe container (3) is arrested by a stop (14), whereupon the frictional force between the plunger and the O-ring is relieved so that the plunger slides forward through the O-ring.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.